

Supurr-Flex Aluminium Ducting

**FO408B, FO503M, FO603M, FO803M,
FUL0425, FUL0525, FUL0625 & FUL0825**

Flexible multi-layered metallic ducting is ideal for general purpose ventilation and can be easily navigated around tight bends.

The multi-purpose ducting can be used for low to medium pressure exhaust venting of bathrooms, electric clothes dryers and other applications.



Key Benefits

- **Complies with Australian Standards - AS1668.1**
- **4 - Zero fire rating to Australian Standards - 1530.3**
- **Temperature rating -18 °C to +130 °C**

Performance

- **Maximum Velocity:** 5000 FPM / 25 m/sec
- **Maximum Rated Pressures:** All diameters 10"(25.4cm) W.C./2.5 Kpa Pos. 2-10" (5.1-25.4cm) dia.: 0.5" W.C./12 Kpa Neg.
- **Operating Temperature Range:** -18°C to 130°C
- **C-UL-US Listed Class 1:** For installations 4.3m or less: UL 181, ULC S110
- **Flame Spread/Smoke Developed:** Flame spread: under 25' (7.6m), Smoke developed: under 50

2.4 Metre Length Duct

Model No.	Description	Diameter (mm)	Length (M)	Packaging
FO408B	Supurr-Flex Ducting (100mm)	100	2.4	Retail

3 Metre Length Duct

Model No.	Description	Diameter (mm)	Length (M)	Packaging
FO503M	Supurr-Flex Ducting (125mm)	125	3	Retail
FO603M	Supurr-Flex Ducting (150mm)	150	3	Retail
FO803M	Supurr-Flex Ducting (200mm)	200	3	Retail

7.6 Metre Length Duct

Model No.	Description	Diameter (mm)	Length (M)	Packaging
FUL0425	Supurr-Flex Ducting (100mm)	100	7.6	Retail
FUL0525	Supurr-Flex Ducting (125mm)	125	7.6	Retail
FUL0625	Supurr-Flex Ducting (150mm)	150	7.6	Retail
FUL0825	Supurr-Flex Ducting (200mm)	200	7.6	Retail